

**CX 14: great power and stability**

The CX14 powered truck is available in several versions. They are suitable for carrying loads on smooth floors and other surfaces. The small size and turning radius make the CX14 range ideal for work in areas where space is at a premium, such as lorries or narrow aisles.



MODEL			CX 1150X525	CX 1150X685	CX 1150X525 PLUS	CX 1150X685 PLUS	CX 1000X525	CX 1000X685	CX 1000X525 PLUS	CX 1000X685 PLUS
CAPACITY	Nominal load	Kg	1400	1400	1400	1400	1400	1400	1400	1400
ELEVATION	Elevation	mm	200	200	200	200	200	200	200	200
	Normal free elevation	mm	115	115	115	115	115	115	115	115
LENGTH	Fork length / Total length	mm	1150 / 1585	1150 / 1585	1150 / 1585	1150 / 1585	1000 / 1435	1000 / 1435	1000 / 1435	1000 / 1435
DIMENSIONS	Fork width x thickness / Width	mm	720 / 525	720 / 685	720 / 525	720 / 685	720 / 525	720 / 685	720 / 525	720 / 685
SPEED	Translation with / without load	Km/h	4,5/4,7	4,5/4,7	4,5/4,7	4,5/4,7	4,5/4,7	4,5/4,7	4,5/4,7	4,5/4,7
	Lifting with / without load	m/s	0,02/0,03	0,02/0,03	0,02/0,03	0,02/0,03	0,02/0,03	0,02/0,03	0,02/0,03	0,02/0,03
	Descent with / without load	m/s	0,04	0,04	0,04	0,04	0,04	0,04	0,04	0,04
MAX SUP. SLOPES	With / without load	%	5/10	5/10	5/10	5/10	5/10	5/10	5/10	5/10
EMPTY WEIGHT	With battery	Kg	203	207	246	250	199	203	242	246
	Traction/starter		STARTER	STARTER	TRACTION	TRACTION	STARTER	STARTER	TRACTION	TRACTION
BATTERY	Voltage/capacity	V/Ah	24/70	24/70	24/100*	24/100*	24/70	24/70	24/100*	24/100*
	Weight	Kg	36	36	78	78	36	36	78	78
BATTERY CHARGER		V/A	24/13	24/13	24/20	24/20	24/13	24/13	24/20	24/20

\* Battery capacity of 130 Ah in 20 hours rating



**Handle with drives**

The ergonomic handle guarantees ease of use, with a battery charge LED indicator and lifting and lowering control.



**Maximum pressure valve**

When maximum load capacity is exceeded, the oil pressure exceeds its maximum limit and the valve automatically stops the forks from lifting. This prevents possible structural damage.



**Safety push-button**

If the machine makes contact with the operator during reversing manoeuvres, the safety push button sends a signal to the drive unit, automatically putting the machine into forward gear, and sounds an alarm.

**Electronic Monitoring**

Electronic monitoring prevents raising of the forks if the battery charge level is too low.



**Traction battery**

The Plus version has a very powerful battery (100Ah) that gives better endurance.



**Stabilising wheels**

Two adjustable wheels allow ease of movement, even on the most difficult of surfaces. The wheels also provide great stability under all conditions.

**Removable Start Key**

The start key starts and stops the truck, also doubling as a parking and safety brake.



The producer reserves the right to introduce changes to models and features without prior notice.

**Pramac Service and Parts**

Pramac Service and Parts is the division responsible for fulfilling Parts and Service requests from our customers. Our intention is to provide a comprehensive and highly professional service, to satisfy any requirements, backed up with a great range of components.

For information about the nearest Pramac Service and Parts Centre:

- Web Site: [www.pramac.com](http://www.pramac.com)

Certifications	Warranty
<ul style="list-style-type: none"> <li>• ISO 9001</li> </ul>  <p>CONFORMS TO THE EUROPEAN SAFETY RULES</p>	<ul style="list-style-type: none"> <li>• 12 months warranty</li> </ul>

**AUTHORIZED DEALER**